

Syndicate file format

(This is the reference for coding libsyndicate)

1st May 2007

The libsyndicate project is in no way affiliated with Electronic Arts and/or Bullfrog
Entertainment.

Syndicate and Bullfrog are trademarks of Electronic Arts.

Syndicate is © 1993 Electronic Arts.

Contents

1	Introduction	6
2	List of files and types	6
2.1	List of data files	6
2.2	List of data types	8
3	File format	9
3.1	RNC	9
3.2	Palette	9
3.3	Font	10
3.4	Req	11
3.5	MapData	11
3.6	MapColumn	12
3.7	MapTile	13
3.8	SpriteAnim	14
3.9	SpriteFrame	15
3.10	SpriteElement	16
3.11	SpriteTab	16
3.12	SpriteData	17
3.13	Mission	17
3.14	Game	18
3.14.1	Common structure	19
3.14.2	Pedestrians	21
3.14.3	Vehicles	23
3.14.4	Objects	23
3.14.5	Weapons	24
3.14.6	Sfx	25
3.14.7	Mapinfos	26
3.14.8	Objectives	26
3.15	Fli	27
3.16	Raw	27
4	Matrix of missions, maps, and games	28
5	Menus sequence	29
6	Equipement guide	29
7	Agents names	30
8	Methods and tools	30

8.1	Cheat codes	30
8.2	Hexadecimal editor	30
8.3	Opened files	32
8.4	Strings	32
8.5	Memdumps	32
9	References	33
10	TODO	33

1 Introduction

This is a documentation that resume informations that was needed to code the libsyndicate.

Thanks to :

- [Jon skeet for dernc.](#)
- [Andrew Sampson for the first reverse ingenering of graphic files.](#)
- [Marcin Olak and the Desyndicate wiki.](#)
- [Stuart Binge, Joost Peters, Trent Waddington and the freesynd project staff.](#)
- [Tomasz Lis for his fan site that resume the whole above.](#)
- [Mike Melanson for details on fli files.](#)

2 List of files and types

2.1 List of data files

This is a list of files with the type of data. Types of data are defined in section [2.2](#).

The prefix 'h' could mean Hight resolution. For example there are HPOITNER.DAT and LPOINTER.DAT.

The prefix 'm' could mean menu.

The prefix 'i' could mean intro.

File	Type	Comment
COL01.DAT	MapColumn	Gives the type for each of the 256 tiles
GAME[xx].DAT	Game	The description of the games
HBLK01.DAT	MapTile	The 256 base tiles that compund maps
HELE-0.ANI	SpriteElement	The descriptions of sprite elements
HFNT01.DAT	Font	FIXME : don't know for what is it used ?
HFRA-0.ANI	SpriteFrame	The descriptions of sprite frames
HPAL01.DAT	Palette	palettes for maps
HPAL02.DAT	Palette	
HPAL03.DAT	Palette	
HPAL04.DAT	Palette	
HPAL05.DAT	Palette	
HPALETTE.DAT	Palette	FIXME
HPOINTER.DAT	SpriteData	arrow, pick, target, pointers
HPOINTER.TAB	SpriteTab	
HREQ.DAT	GameFont	Fonts used for the game screen
HSPR-0.DAT	SpriteData	sprites for maps
HSPR-0.TAB	SpriteTab	
HSTA-0.ANI	SpriteAnim	The descriptions of sprite anims

File	Type	Comment
INTRO.DAT	Fli	Animation for the introduction
INTRO.XMI	Music	Music for the introduction
ISNDS-0.DAT	SoundData	FIXME
ISNDS-0.TAB	SoundTab	FIXME
ISNDS-1.DAT	SoundData	FIXME
ISNDS-1.TAB	SoundTab	FIXME
MAP[xx].DAT	MapData	Map data (tiles reconstitution)
MBRIEF.DAT	Fli	
MBRIEOUT.DAT	Fli	
MCONFOUT.DAT	Fli	
MCONFUP.DAT	Fli	
MCONSCR.DAT	Raw	
MDEBRIEF.DAT	Fli	
MDEOUT.DAT	Fli	
MENDLOSE.DAT	Fli	
MENDWIN.DAT	Fli	
MFNT-0.DAT	SpriteData	The menu fonts (rle encoded)
MFNT-0.TAB	SpriteTab	
MGAMEWIN.DAT	Fli	
MISS[xx].DAT	Mission	Defines the mission objectives etc.
MLOGOS.DAT	Raw	
MLOSA.DAT	Fli	
MLOSAOUT.DAT	Fli	
MLOSEGAM.DAT	Fli	
MMAP.DAT	Fli	
MMAPBLK.DAT	Raw	
MMAPOUT.DAT	Fli	
MMINLOGO.DAT	Raw	
MMULTI.DAT	Fli	
MMULTOUT.DAT	Fli	
MOPTION.DAT	Fli	
MOPTOUT.DAT	Fli	
MRESOUT.DAT	Fli	
MRESRCH.DAT	Fli	
MSCRENUP.DAT	Fli	
MSELECT.DAT	Fli	
MSELECT.PAL	Palette	Palette for the menus
MSELOUT.DAT	Fli	
MSPR-0.DAT	SpriteData	The menu sprites (rle encoded)
MSPR-0.TAB	SpriteTab	
MTITLE.DAT	Fli	
SAMPLE.AD	Audio/sound	
SAMPLE.OPL	Audio/sound	
SOUND-0.DAT	SoundData	
SOUND-0.TAB	SoundTab	
SOUND-1.DAT	SoundData	

File	Type	Comment
SOUND-1.TAB	SoundTab	
SYNGAME.XMI	Music	

Table 1: Table of files.

2.2 List of data types

This is a list of types.

Type	Reverse	Files associated
Fli		INTRO.DAT INTRO.XMI MBRIEF.DAT MBRIEOUT.DAT MCONFOUT.DAT MCON- FUP.DAT MCONSCR.DAT MDEBRIEF.DAT MDEOUT.DAT MENDLOSE.DAT MEND- WIN.DAT MGAMEWIN.DAT MLOSA.DAT MLOSAOUT.DAT MLOSEGAM.DAT MMAP.DAT MMAPOUT.DAT MOPTION.DAT MOPTOUT.DAT MRESOUT.DAT MRES- RCH.DAT MSCRENUP.DAT MSELECT.DAT MSELOUT.DAT MTITLE.DAT MMULTI.DAT MMULTOUT.DAT
Font	100%	HFNT01.DAT
Game	25%	GAME[xx].DAT
MapColumn	100%	COL01.DAT
MapData	100%	MAP[xx].DAT
MapTile	100%	HBLK01.DAT
Mission	100%	MISS[xx].DAT
Music		SYNGAME.XMI
Palette	100%	HPAL[xx].DAT HPALETTE.DAT MSELECT.PAL
Raw	100%	MLOGOS.DAT MMAPBLK.DAT MMINL- OGO.DAT
Req	75%	HREQ.DAT
SoundData		ISNDS-[x].DAT SOUND-[x].DAT
SoundTab		ISNDS-[x].TAB SOUND-[x].TAB
SpriteAnim	100%	HSTA-0.ANI
SpriteFrame	75%	HFRA-0.ANI
SpriteElement	100%	HELE-0.ANI
SpriteTab	100%	HPOINTER.TAB HSPR-0.TAB MFNT-0.TAB MSPR-0.TAB
SpriteData	100%	HPOINTER.DAT HSPR-0.DAT MFNT-0.DAT MSPR-0.DAT

Table 2: Table of types.

3 File format

The fields are integers only, so we will use the standard int types. We prefix them with `le_` if it's coded in little endian, with `be_` else. For example, if a field is a 16 bit unsigned integer, coded in little endian we call it `le_uint16_t`.

We will also use a base type called `Block`. They will be explained later.

3.1 RNC

The files are compressed with a tool called Pro-Pack from Rob Northern Computing.

The header is in big endian.

```
struct
{
    be_uint32_t  _signature;
    be_uint32_t  _unpacked_lenght;
    be_uint32_t  _packed_lenght;
    be_uint16_t  _unpacked_crc;
    be_uint16_t  _packed_crc;
    be_uint8_t   _unknown;
    be_uint8_t   _number_of_pack;
} _header;
```

The signature is always `0x524E4301` ("RNC "). Other fields are self-explained.

Then, there is two bits. I don't know what is it, but they always seem to be set to zero.

Then the compressed data comes by packet. It seems that an uncompressed packet can make 12280 bytes max. A packet begins with three Huffman tables.

Each Huffman table begins with 5 bits that give the max value of the nodes, then 4 bits for each value that give the depth of their node.

After the three tables, there are 16 bits that give the number of chunks.

A chunk is a sequence of raw data, and a copy of a previous sequence.

The length of the raw data is taken from the first Huffman table. The node in the Huffman table is found with the first bits we get from the stream. Then, if the value of the node is `FIXME`.

3.2 Palette

The Palette files are : `HPAL[xx].DAT`, `HPALETTE.DAT`, `MSELECT.PAL`.

Their structure is :

```
struct {
    struct {
        uint8_t _r;
        uint8_t _g;
        uint8_t _b;
    } _rgb[256];
};
```

There are 16 colours defined, and the value are between 0 and 63 (ie 7 bits).

For an 8 bits system, we need to scale the values between 0 and 255.

3.3 Font

The Font file is : HFNT01.DAT.

His structure is :

```
struct
{
    struct
    {
        le_uint16_t _offset;
        le_uint8_t _width;
        le_uint8_t _height;
        le_uint8_t _line_offset;
    } _tab[128];
    le_uint8_t _data[];
};
```

_offset is the offset in the **_data** array,

_width is the width of the font,

_height is the height,

_line_offset is the vertical offset where to draw the font from the top (FIXME : check),

_data are the data.

The pixel are coded with one bit.

If the width is strictly less than 8, each line is coded as **le_uint8_t** where each bit represent a pixel.

If the width is greater or equal than 8, each line is coded as **le_uint16_t** where each bit represent a pixel. So the first pixel is the eighth bit, the last pixel is the seventh.

3.4 Req

FIXME : find a better name for this.

The Req file is : HREQ.DAT.

His structure is :

```
struct
{
    struct
    {
        Block840    _lines [ _height ];
        le_uint8_t  _spares [16];
    } _entries [];
};
```

Theses data are fonts. They are 8 width and 16 height. The pixel are packed by line. So we have 16 block of 8 pixels.

A block of 8 pixel is 16 bytes. The pixels are coded on 4 bits in little endian.

- There are 32 bits for the lsb of the index of each pixels.
- There are 32 bits for the [].
- There are 32 bits for the [].
- There are 32 bits for the msb of the index of each pixels.

So they are coded as follow :

```
struct
{
    le_uint32_t  _bit_0 ;
    le_uint32_t  _bit_1 ;
    le_uint32_t  _bit_2 ;
    le_uint32_t  _bit_3 ;
};
```

So bit 0 of pixel 0 is the 7th bit of _bit_0 and bit 0 of pixel 32 is the 24th bit of _bit_0.

FIXME : some fields are unknown. Moreover there isn't alpha channel, so should we consider a value as transparent ?

3.5 MapData

The MapData files are : MAP[xx].DAT.

His structure is :

```
struct {
    le_uint32_t  _nb_i;
    le_uint32_t  _nb_j;
    le_uint32_t  _nb_k;
    le_uint32_t  _offset [ _nb_i * _nb_j ];
```

```

    le_uint8_t  _tile[??? * _nb_k];
};

```

`_nb_i` is the number of tiles on i,

`_nb_j` is the number of tiles on j,

`_nb_k` is the number of tiles on k,

`_offset` is a table with the offset (from byte 12) of the tiles index,

`_tile` are the tiles index packed by stack.

For example, if we want the tile at (i;j;k), it is `_tile[_offset[j * _nb_i + i] * _nb_k + k]`

The figure 1 illustrate the components of a map.




Figure 1: A map.

3.6 MapColumn

The MapColumn file is : COL01.DAT.

His structure is :

```

struct
{
    le_uint8_t  _type[256];
};

```

This file give the type of each tiles from HBLK01.DAT :

```
enum ColType
{
    None ,
    SlopeSN ,
    SlopeNS ,
    SlopeEW ,
    SlopeWE ,
    Ground ,
    RoadEW ,
    RoadWE ,
    RoadSN ,
    RoadNS ,
    Wall ,
    CrossRoad ,
    HandrailLight ,
    Roof ,
    EmergencyArea ,
    Rail ,
};
```

The “CrossRoad” seems to be a support for “feux de signalisation” (FIXME).

3.7 MapTile

The MapTile file is : HBLK01.DAT.

His structure is :

```
struct
{
    le_uint32_t _offset [256][6];
    struct {
        Block32 _lines [16]
    } _subtile [986];
};
```

A tile is 64 pixels width and 48 pixels height. It is compound of 6 subtiles.

Each subtile is 32 pixels width and 16 pixels height. The pixel are packed by line. So we have 16 block of 32 pixels.

A block of 32 pixel is 20 bytes. The pixels are coded on 5 bits in big-endian : one for the transparency and 4 for the index in the palette :

- There are 32 bits for the transparency bits of each pixels.
- There are 32 bits for the lsb of the index of each pixels.
- There are 32 bits for the [].
- There are 32 bits for the [].

- There are 32 bits for the msb of the index of each pixels.

So they are coded as follow :

```
struct
{
    be_uint32_t _alpha;
    be_uint32_t _bit_0;
    be_uint32_t _bit_1;
    be_uint32_t _bit_2;
    be_uint32_t _bit_3;
};
```

The figure 2 illustrate the components of a map tile.




Figure 2: Tiles, Subtiles and blocks.

3.8 SpriteAnim

The SpriteAnim file is : `HSTA-0.ANI`.

His structure is :

```
struct
{
    le_uin16_t _indexes [];
}
```

This is an array of frame index. So the first frame of the 5th animation is given by `_indexes[5]`. Then the others frames are given in the `SpriteFrame` array.

The figure 3 illustrate the components of an animation.




Figure 3: Components of an animation.

3.9 SpriteFrame

The `SpriteFrame` file is : `HFRA-0.ANI`.

His structure is :

```
struct
{
    struct
    {
        le_uint16_t _first;
        le_uint8_t _width;
        le_uint8_t _height;
```

```
    le_uint16_t  _flags;
    le_uint16_t  _next;
}  _frames  [];          // FIXME : give the number of frames
};
```

This is an array of frame description. A frame has a width, height, some flags and is compound of sprite elements. The index of the first sprite element is `_first`. This is an index (not an offset) in the Sprite Element tab file (see 3.10). The index of the next frame is given by `_next`. The frame index automatically loop to the first frame.

Not sure but the `_flags` field seems to be 0x1000 when it is the first frame of an animation. The frame 1450 is the persuadotron in the inventory. Then every 6 index, there is the next weapon.

3.10 SpriteElement

The SpriteElement file is : HELE-0.ANI.

His structure is :

```
struct
{
    struct
    {
        le_uint16_t  _sprite;
        le_int16_t   _x_offset;
        le_int16_t   _y_offset;
        le_uint16_t  _x_flipped;
        le_uint16_t  _next;
    }  _elements [];      // FIXME : give the number of elements
};
```

The `_sprite` field give the index (not an offset) in the sprite tab file (see 3.11). The `_next` is the index of the next element. If it is zero there isn't any more elements. The `_x_flipped` attribut tells if it is horizontally flipped.

3.11 SpriteTab

The SpriteTab file are : HPOINTER.TAB, HSPR-0.TAB, MFNT-0.TAB, MSPR-0.TAB.

Their structure is :

```
struct
{
    struct
    {
        le_uint32_t  _offset;
        le_uint8_t   _width;
        le_uint8_t   _height;
    }  _entries [];      // FIXME : give the number of entries
};
```

The offset give the number of bytes to skip from the begining of the sprite data file (see 3.12).

FIXME : give the aproprate palette for each file.

3.12 SpriteData

The SpriteData file are : HPOINTER.DAT, HSPR-0.DAT, MFNT-0.DAT, MSPR-0.DAT.

Their structure is :

```
struct
{
    le_uint16_t  _nb_sprites;
    union
    {
        Block8      _blocks [];
        le_uint8_t  _rle [];
    } _data;
};
```

The sprite datas are encoded as lines of pixels (structured as block) or as rle datas.

The `_nb_sprite` field gives the number of sprites. It seems that when it is not zero, the data are encoded as rle (the flag is 0x0053 for MSPR-0.DAT and 0x00CD for MFNT-0.DAT). Else, the datas are encoded as lines of pixels (structured in blocks).

If the pixel are packed by line, each line is one or more block of eight pixels. A block is 5 bytes : one for the transparency and 4 for the index in the palette.

- There are 8 bits for the transparency bits of each pixels.
- There are 8 bits for the lsb of the index of each pixels.
- There are 8 bits for the
- There are 8 bits for the
- There are 8 bits for the msb of the index of each pixels.

3.13 Mission

The Mission file are : MISSXX.DAT. They contain text and available in 4 language :

english from 01 to 50

french from 101 to 150

italian from 201 to 250

german from 301 to 350

Each string is separated with an EOL (0x0a). Other separator is the pipe '—' (0x7c).

3.14 Game

The Game file are : **GAMEXX.DAT**.

Their structure is :

```
struct GameStruct
{
    le_uint8_t      _header[6];
    le_uint16_t     _offsets[128][128];
    le_uint16_t     _offset_ref;           // (32774)
    struct Pedestrian _pedestrians[256];  // 0x0:8008 (32776)
    struct Vehicle   _vehicles[64];       // 0x0:DC08 (56328)
    struct Object    _objects[400];       // 0x0:E688 (59016)
    struct Weapon    _weapons[512];       // 0x1:1568 (71016)
    struct Sfx       _sfx[256];           // 0x1:5D68 (89448)
    le_uint8_t      _unkn08[2048 * 8];    // 0x1:7B68 (97128)
    le_uint8_t      _unkn09[427];         // 0x1:BB68 ()
    struct Mapinfos  _mapinfos;           // 0x1:BD1D (113949)
    struct Objectives _objectives[7];      // 0x1:BD36 (113974)
    le_uint8_t      _unkn11[129 * 15];    // 0x1:BD98 ()
};
```

The header could be two **ints** that are seeds for example (FIXME, not sure).

The **_offsets** field is an array that represent the tiles of the map (every map are 128x128 tiles). The values plus 32774 give an offset in this file that is the entity placed on this tile. The resulting offset can be 98309 max and only peds, vehicle, objects and weapons can be indexed.

It is used for the minimap in the breifing menu. As a clue, for the first level, there are three red points, that are in the **_offsets** array. It is also probably (not sure) used for te minimap in the game.

The values for offset are :

- [2; 23554[pedestrian
- [23554; 26242[vehicle
- [26242; 38242[objects
- [38242; 56674[weapons
- [56674; 64354[sfx

The **_unkn07** field is a structure of 12 bytes.

The **_unkn08** field is an array of 2048 structures of 8 bytes. Perhaps it as something to do with A.I.

The **_unkn09** field is a structure of 437 bytes.

The **_unkn11** field is an array of 129 structures of 15 bytes.

There are 116010 bytes in all files.

3.14.1 Common structure

The Pedestrian, Vehicle, Object and Weapon have a common header like this :

```
struct
{
    le_uint16_t  _offset_next;
    le_uint16_t  _offset_prev;
    le_uint16_t  _tile_i;
    le_uint16_t  _tile_j;
    le_uint16_t  _tile_k;
    le_uint8_t   _unkn10;
    le_uint8_t   _unkn11;
    le_uint8_t   _unkn12[2];
    le_uint16_t  _index_base_anim;
    le_uint16_t  _index_current_frame;
    le_uint16_t  _index_current_anim;
    le_int16_t   _health;
    le_uint16_t  _offset_unknown;
    le_uint8_t   _type;
    le_uint8_t   _status;
    le_uint8_t   _orientation;
};
```

The `_offset_prev` and `_offset_next` plus 32774 gives the offset in this file of the previous and next entity. This is probably used for drawing the scene. I think that for drawing the scene the pseudo-algo could be :

```
for (k = 0; k < max_k; k++)
    for(j = 0; j < 128; j++)
        for(i = 0; i < 128; i++)
            draw(tile[j * 128 + i]);
            if(_offsets[j * 128 + i]._tile_k >> 8 == k)
                entity = _offsets[j * 128 + i]
                while(entity)
                {
                    draw(entity)
                    entity = entity._offset_next
                }
```

The `_tile_*` give the location of the entity on the map along i, j or k. Each tile is a cube of side 256 (see fig. 1). We can deduce the tile id dividing by 256.

The `_unkn10` is unknown but contain 0x04 for peds, 0x05 for weapons (FIXME check this).

The `_index_base_anim` give an index (not an offset) in the file `HSTA-0.ANI`. It is the base offset for the animation of this ped.

The `_index_current_frame` give an index (not an offset) in the file `HFRA-0.ANI`. It is the current frame of the current animation displayed.

The `_index_current_anim` give an index (not an offset) in the file `HSTA-0.ANI`. It is the current animation.

The `health` give the ressources of the element. For a pedestrian it will be the health, for a weapon, the `ammo`. I'am not sure it's alwas a signed int.

The `_offset_unknown` added to 32774 give an offset in this file. This seems to be a kind of “dependency” (see section 3.14.2).

The `_type` give the type of objects :

- 0x01 ped,
- 0x02 vehicle,
- 0x04 weapon,
- 0x05 object.

For example, it allow to display a target or a pickup on the game screen or for the minimap.

The `_status` may contain informations about the status of the object, or for weapons the “subtype”.

The `_orientation` give the initial orientation (illustrated on fig. 4) of the element :

- from 0xF0 to 0x10 : south
- from 0x10 to 0x30 : south-east
- from 0x30 to 0x50 : east
- from 0x50 to 0x70 : east-north
- from 0x70 to 0x90 : north
- from 0x90 to 0xB0 : north-west
- from 0xB0 to 0xD0 : west
- from 0xD0 to 0xF0 : west-south




Figure 4: Orientation of the ped is given i black (0x20 represent 45 degree). The offset of the animation if the ped doesn't move is given in red. And the offset of the ped if he moves is given in blue.

3.14.2 Pedestrians

The `_pedestrians` is an array of 256 structures that describe pedestrians. This array is at address 32776 (0x8008), and each structure is 92 bytes.

```
struct Pedestrian
{
    // - 00
    le_uint16_t _offset_next;
    le_uint16_t _offset_prev;
    le_uint16_t _tile_i;
    le_uint16_t _tile_j;
    le_uint16_t _tile_k;
    // - 10
    le_uint8_t _unkn10;
    le_uint8_t _unkn11;
    le_uint8_t _unkn12;
    le_uint8_t _unkn13;
    le_uint16_t _index_base_anim;
    le_uint16_t _index_current_frame;
    le_uint16_t _index_current_anim;
    // - 20
    le_int16_t _health;
    le_uint16_t _offset_last_enemy;
    le_uint8_t _type;
    le_uint8_t _status;
    le_uint8_t _orientation;
    le_uint8_t _unkn27;
    le_uint8_t _unkn28;          // when 01 pedestrian, 02 agent, 04 police, 0
    le_uint8_t _unkn29;
    // - 30
    le_uint16_t _unkn30;
    le_uint16_t _offset_of_persuader;
    le_uint16_t _unkn34;
    le_uint16_t _offset_of_vehicle;
    le_uint16_t _unkn38;
    // - 40
    le_uint16_t _unkn40;
    le_uint16_t _unkn42;
    le_uint16_t _offset_of_vehicle;
    le_uint16_t _goto_tile_i;
    le_uint16_t _goto_tile_j;
    // - 50
    le_uint16_t _goto_tile_k;
    le_uint8_t _unkn52[6];
    le_uint16_t _offset_equipment;
    // - 60
    le_uint16_t _mods_info;
    le_uint8_t _unkn62[6];
}
```

```

    le_uint16_t  _offset_cur_weapon;
    // - 70
    le_uint8_t   _unkn70;
    le_uint8_t   _adrena_amount;
    le_uint8_t   _adrena_dependency;
    le_uint8_t   _adrena_effect;
    le_uint8_t   _unkn74;
    le_uint8_t   _inteli_amount;
    le_uint8_t   _inteli_dependency;
    le_uint8_t   _inteli_effect;
    le_uint8_t   _unkn78;
    le_uint8_t   _percep_amount;
    le_uint8_t   _percep_dependency;
    le_uint8_t   _percep_effect;
    le_uint8_t   _unkn82;
    le_uint8_t   _unkn83[9];
};

```

The `_unkn10` seems to be 4.

The `_health` of our agent can be 0x10 maximum. When it is less than zero the ped should die.

The `_sub_type` is used for minimap for example (colored dots) and can be (FIXME):

- agent
- enemy agent
- criminals
- civilian
- police
- guard

The `_offset_last_enemy` is the offset of the last peds that hurt, or persuade this ped (Not really sure).

The `_offset_equipment + 32774'` gives the offset in this file of the first equipment of this ped.

The `_mods_info` gives the level of the mods. It its a bitfield with two bits for each mods :

msb									lsb
spare		brain	eye	heart	chest	arm	leg	gender	

The gender is 1 for femele and 0 for male.

The `_offset_cur_weapon + 32774'` gives the offset in this file of the current weapon in use.

The IPA levels seems to have 4 bytes. At least 3 bytes are sure. They are discribed on the picture [5](#).




Figure 5: Detail of IPA field.

3.14.3 Vehicles

The `_vehicles` is an array of 64 structures that describe vehicles. This array is at adress 56328 (0xDC08), and each structure is 42 bytes.

```
struct Vehicle
{
    le_uint16_t _offset_next;
    le_uint16_t _offset_prev;
    le_uint16_t _tile_i;
    le_uint16_t _tile_j;
    le_uint16_t _tile_k;
    le_uint8_t _unkn10;
    le_uint8_t _unkn11;
    le_uint8_t _unkn12;
    le_uint8_t _unkn13;
    le_uint16_t _index_base_anim;
    le_uint16_t _index_current_frame;
    le_uint16_t _index_current_anim;
    le_int16_t _health;
    le_uint16_t _offset_last_enemy;
    le_uint8_t _type;
    le_uint8_t _sub_type;
    le_uint8_t _orientation;
    le_uint8_t _unkn27;
    le_uint8_t _offset_of_ped;
    le_uint8_t _unkn30[13];
};
```

The `_offset_of_ped + 32774'` gives the offset in this file of the first ped in this vehicle.

3.14.4 Objects

The `_objects` is an array of 400 structures that describe objects (trees, doors, windows, etc.). This array is at adress 59016 (0xE688), and each structure is 30 bytes.

```
struct Object
{
    le_uint16_t _offset_next;
    le_uint16_t _offset_prev;
```

```
le_uint16_t  _tile_i;
le_uint16_t  _tile_j;
le_uint16_t  _tile_k;
le_uint8_t   _unkn10;
le_uint8_t   _unkn11;
le_uint8_t   _unkn12;
le_uint8_t   _unkn13;
le_uint16_t  _index_base_anim;
le_uint16_t  _index_current_frame;
le_uint16_t  _index_current_anim;
le_uint8_t   _unkn20[4];
le_uint8_t   _type;
le_uint8_t   _sub_type;
le_uint8_t   _orientation;
le_uint8_t   _unkn27[3]; // always 0 ?
};
```

The `_sub_type` can be : 0x0C door, 0x12 open window, 0x13 close window, 0x16 tree,

The `_unkn27` seems to be always zero.

3.14.5 Weapons

The `_weapons` is an array of 512 structures that describe weapons. This array is at adress 71016 (0x11568), and each structure is 36 bytes.

```
struct Weapon
{
    le_uint16_t  _offset_next;
    le_uint16_t  _offset_prev;
    le_uint16_t  _tile_i;
    le_uint16_t  _tile_j;
    le_uint16_t  _tile_k;
    le_uint8_t   _unkn10;
    le_uint8_t   _unkn11;
    le_uint8_t   _unkn12;
    le_uint8_t   _unkn13;
    le_uint16_t  _index_base_anim;
    le_uint16_t  _index_current_frame;
    le_uint16_t  _index_current_anim;
    le_uint16_t  _nb_amos;
    le_uint16_t  _unkn22;
    le_uint8_t   _type;
    le_uint8_t   _sub_type;
    le_uint16_t  _unkn26;
    le_uint16_t  _offset_next_inventory;
    le_uint16_t  _offset_prev_inventory;
    le_uint16_t  _offset_owner;
    le_uint16_t  _unkn34;
};
```

```
| };
```

The `_sub_type` can be :

- 0x01 persuadertron,
- 0x02 pistol / air raid com,
- 0x03 gauss gun,
- 0x04 shotgun,
- 0x05 uzi,
- 0x06 minigun,
- 0x07 laser,
- 0x08 flamer,
- 0x09 long range,
- 0x0A scanner,
- 0x0B medikit,
- 0x0C time bomb,
- 0x0D access card / clone shield,
- 0x0E invalid,
- 0x0F invalid,
- 0x10 invalid,
- 0x11 energy shield.

The `_nb_amos` is the number of amos remaining. If the weapon is empty, it is equal to 0xffff (and the weapon is not selectable).

FIXME : is there any info for the picture of the weapon in the inventory ?

3.14.6 Sfx

The `_sfx` is an array of 256 structures that describe sfx (for the flamer, the gauss gun, etc.). This array is at adress 89448 (0x15D68), and each structure is 30 bytes.

```
struct Sfx
{
    le_uint16_t _offset_next;
    le_uint16_t _offset_prev;
    le_uint16_t _tile_i;
    le_uint16_t _tile_j;
    le_uint16_t _tile_k;
```

```
le_uint16_t _unkn10;
le_uint16_t _unkn12;
le_uint16_t _index_base_anim;
le_uint16_t _index_current_frame;
le_uint16_t _index_current_anim;
le_uint16_t _unkn20;
le_uint16_t _unkn22;
le_uint16_t _unkn24;
le_uint16_t _unkn26;
le_uint16_t _offset_owner;
};
```

3.14.7 Mapinfos

The `_mapinfos` is a structure that describe the map. This is at adress 113949 (0x1BD1D), and the structure is 25 bytes.

```
struct Mapinfos
{
    le_uint8_t _unkn00[11];
    le_uint16_t _map;
    le_uint16_t _min_x;
    le_uint16_t _min_y;
    le_uint16_t _max_x;
    le_uint16_t _max_y;
    le_uint8_t _unkn10[4];
};
```

The `_map` gives the number of the map. For example, if `_map` is 9 the map we should open is MAP09.DAT.

3.14.8 Objectives

The `_objectives` is an array of 7 structures that describe the objectives of the mission. This array is at adress 113974 (0x1BD36), and the structure is 14 bytes.

```
struct Objectives
{
    le_uint16_t _type;
    le_uint16_t _offset;
    le_uint16_t _tile_i;
    le_uint16_t _tile_j;
    le_uint16_t _tile_k;
    le_uint8_t _unkn10[4];
};
```

The `_type` field can be : 0x00 ??? ,0x01 persuade, 0x02 assassinate, 0x03 protect, 0x05 equipment aquisition, 0x0a combat sweep (police), 0x0b combat sweep, 0x0d raid and rescue, 0x0e use/destroy vehicle, 0x10 evacuate.

The `_offset + 32774` gives the offset in this file of the objective.

If “protect”, the next objective are the goals and their type is zero. The list finish with zero and the offset of the protected item ? FIXME.

3.15 Fli

The Fli files are : `INTRO.DAT`,

There are some specific informations about Bullfrog fli files at <ftp://ftp.mplayerhq.hu/MPlayer/samples/formats/magiccarpet-fli/>.

A description of fli can be found at :

- <http://www.martinreddy.net/gfx/anim/FLI.txt>,
- <http://steve.hollasch.net/cgindex/formats/fli.html>,
- http://www.textfiles.com/programming/FORMATS/fli_flc.txt.

Other descriptions can be found at :

- <http://www.fileformat.info/format/fli/>
- <http://www.compuphase.com/flic.htm>

There are some difference with the original description. The header is :

```
struct {
    le_uint32_t  _size;
    le_uint16_t  _magic;
    le_uint16_t  _frames;
    le_uint16_t  _width;
    le_uint16_t  _height;
};
```

The `_size` give the size of the header.

3.16 Raw

The Raw files are : `MCONSCR.DAT`, `MLOGOS.DAT`, `MMAPBLK.DAT`, `MMINLOGO.DAT`.

These files gives raw pixels.

File	Nb of pictures	Dimension of each picture
MCONSCR	1	320x200
MLOGOS	40	32x32
MMAPBLK	50	64x44
MMINLOGOS	40	16x16

Table 3: Table of raw files.

4 Matrix of missions, maps, and games

The games from 90 to 99 are used for multiplayer games. The others are the 50th.

Games	Mission	Map	Palette	Country
01	01	01	2	Western Europe
02	02	02	3	Far East
03	03	03	4	Mongolia
04	04	04	5	Iran
05	05	05	1	California
06	06	06	2	Iraq
07	07	07	1	India
08	08	08	4	Northeast Territories
09	09	63	5	Kazakhstan
10	10	10	1	Eastern Europe
11	11	11	2	Western Australia
12	12	12	3	Kanchatka
13	13	13	4	Mozambique
14	14	20	5	Peru
15	15	18	1	Central Europe
16	16	19	2	Greenland
17	17	35	3	Alaska
18	18	38	4	Urals
19	19	34	5	Northern Territories
20	20	32	1	Scandinavia
21	21	39	2	Yukon
22	22	41	3	Siberia
23	23	90	4	Rockies
24	24	70	5	Southern States
25	25	91	1	Indonesia
26	26	92	2	Mexico
27	27	71	3	Zaire
28	28	72	4	Algeria
29	29	40	5	New England
30	30	67	1	Argentina
31	31	93	2	South Africa
32	32	60	3	Colorado
33	33	61	4	Sudan
34	34	62	5	Mid West
35	35	43	1	Lybia
36	36	31	2	Venezuela
37	37	56	3	Atlantic Accelerator
38	38	57	4	Arabia

Games	Mission	Map	Palette	Country
39	39	58	5	Northwest Territories
40	40	63	1	Kenya
41	41	64	2	Mauritania
42	42	66	3	Newfoundland
43	43	65	4	New South Wales
44	44	80	5	Colombia
45	45	81	1	Nigeria
46	46	82	2	Brazil
47	47	50	3	Uruguay
48	48	51	4	Pacific Rim
49	49	53	5	Paraguay
50	50	54	0	China (Palette 0 !!! intresting !)
90		16	1	
91		21	1	
92		02	1	
93		05	1	
94		43	1	
95		67	1	
96		72	1	
97		90	1	
98		94	1	
99		17	1	

Table 4: Matrix of games, missions and maps.

5 Menus sequence

The menu sequence is depicted on figure 6.

6 Equipement guide

Item	Cost	Range	Ammo	Shot
Persuadetron	5000	256	-	-
Pistol	0	1280	12	0
Guass Gun	50000	5120	3	15000
Shotgun	250	1024	12	2
Uzi	750	1792	50	2
Mini-Gun	10000	2304	500	10
Laser	35000	4096	5	2000
Flamer	1500	512	1000	1
Long Ranger	1000	6144	30	2

Item	Cost	Range	Ammo	Shot
Scanner	500	4096	-	-
Medikit	500	256	1	1
Time Bomb	25000	1000	-	-
Access Card	1000	256	-	-
Energy Shield	8000	768	200	15

Table 5: Table of equipments.

7 Agents names

There are 68 agents :

AFSHAR AARNOLD EBAIRD LTBALDWIN BLACK BOYD PLABOYESEN BRAZIER BROWN RBUSH CARR PLACHRISMAS CLINTON COOPER ECORPES TCOX DAWSON EDONKIN TDISKETT DUNNE EDGAR LAEVANS FAIRLEY FAWCETT FLINT LTFLOYD GRIFFITHS YDHARRIS EHASTINGS HERBERT HICKMAN HICKS LAHILL MASJAMES INJEFFERY JOESEPH JOHNSON JOHNSTON ONKJONES SKLEWIS NNLINDSELL LALOCKLEY MARTIN MCENTEE MCLAUGHIN OYMOLYNEUX ITHMUNRO RRMORRIS TMUMFORD NIXON PARKER PRATT LAREID MASRENNIE NRICE RIPLEY ROBERTSON HNROMANO KSEAT SKSEN SHAW IND-SIMMONS SNELLING TAYLOR TROWERS WEBLEY IWELLESLEY UXWILD UNRWILLIS

8 Methods and tools

8.1 Cheat codes

NUK THEM Select any country

ROB A BANK 100 million

TO THE TOP 100 million and select any country

COOPER TEAM Money and items

WATCH THE CLOCK Fast research completion

DO IT AGAIN Press [Ctrl] + C to finish mission

8.2 Hexadecimal editor

An hexa editor is mandatory. Graphical, ones are handfull when you have to explore only one file a time. For an overview of all files, command line tools are better i think. For example, to see the objectives structures :




Figure 6: The succession of the different menu.

```
for i in `ls GAME*.DAT`;
do
    echo $i; od -A x -j 113974 -N 98 -t x1 --width=14 $i;
done | more
```

8.3 Opened files

To see what files are open, we can use :

```
# strace -e trace=open dosbox -conf dosbox.conf MAIN.EXE &
```

8.4 Strings

Talk abouts strings.

8.5 Memdumps

I use the Memshot tool because it seems that GAMEXX.DAT files are mapped in memory. So if we use dosbox for running Syndicate, we can inspect the dynamic of data in memory. For example :

1. - launch dosbox and enter the level 1

```
# dosbox -conf dosbox.conf MAIN.EXE &
```

2. - get the pid

```
# ps -e
```

3. - use Memshot

```
# ./MemshotFe pid GAME01.DAT [59020 [4]]
?> 1
```

4. - move in the game

5. - use Memshot

```
?> s
```

The game reinit if you took the shot at the beginning of the level !

9 References

- [Infos for rnc algorithm.](#)
- [First reverse ingenering of graphic files.](#)
- [Desyndicate \(reverse ingenering\) wiki.](#)
- [The freesynd project.](#)
- [A fan site.](#)

10 TODO

Probably a lot of things here !